
### **PRODUCT SHEET**

## **LEVEL CONTROLLER - DC-LS-50**



The DC-LS-50 is a robust, easy-to-mount level sensor developed specially for cold stored liquid gases in closed containers like storage tanks, dewars and phase separators. Our DC-LS-50 level sensor can be used for multiple gases like nitrogen, oxygen, argon and carbon dioxide, and it provides an accurate and reliable digital liquid level indication. Readout is possible from a local battery-powered display or continuously from an external control unit.

The electrical capacitance of the sensor increases ratio metrically with the measured liquid height, and is converted into an easy-to-read, accurate digital readout with 0.1% resolution.



#### **FEATURES**

All stainless steel

Deliverable in lengths from 0.2 up to 2 metres

Battery powered and/or loop with life indicator

Readout on request

Ingress protection IP65

Up to 35 bar nominal pressure

Easy to mount

Easy adjustment and calibration



## **PRODUCT SHEET**


# **LEVEL CONTROLLER - DC-LS-50**

TECHNICAL DATA			
Dimension casing	280x218x156mm (LxHxD)		
Material casing	ABS		
Material transp. cover	Polycarbonate		
Power supply	110/240VAC 48-63Hz		
Power output	24VDC		
Ingress protection	IP65		
Measuring input signal	0-20mA/4-20mA or 0-10VDC		
Output alarm relay	Voltage free changeover relay NO, max. 3A at 230VAC		
Output relay On/Off	Voltage free changeover relay NO, max. 3A at 230VAC		
Output analog	0-20mA / 4-20mA R <sub>load</sub> <500Ω		
Power cable	L=5 meter with Type F plug		

(1) Battery life 3-5 years at 3 times/day with an standard Alkaline Battery of 500mAh. Actual battery life depends on storage and operating temperature, time intervals and battery manufacturer.

#### STANDARD STOCK LENGTHS

Demaco	Lengths A	Lengths B	Lengths C
Article No.	(mm)	(mm)	(mm)
522.150	765	430	10
522.160	810	465	10
522.170	1180	800	10





OESTER 2 NL-1723 HW NOORD-SCHARWOUDE T +31 (0)226 33 21 00 E INFO@DEMACO.NL

